

Declaration of Performance
(according to regulation EU No 305/2011)

No. LPE Plate S355N

Plate S355N / 1.0545 according EN 10025-3

To be used in-welded, bolted and riveted structures

Tata Steel UK Limited
Long Products Europe
PO Box 1, Brigg Road
Scunthorpe, DN16 1BP
Tel: +44 (0)1724 404040
Website : www.tatasteeleurope.com

CE Marking Notified Body
Lloyds Register Verification Limited
71 Fenchurch Street, London, EC3M 4BS
Tel :+44 (0)207 423 2428
Email : ecdirectives@lr.org
Website : www.lr.org

System of assessment and verification of constancy of
performance of the product
System 2+

Notified factory production control certification body No. 0038
performed the initial inspection of the manufacturing plant and of
factory production control and the continuous surveillance,
assessment, and evaluation of factory production control and
issued the certificate of conformity of the factory production
control



Jon Bolton – Director, Long Products Europe
Tata Steel UK Limited

1st July 2013
Date

Essential characteristic	Performance		Harmonised technical specification		
	Tolerances on dimensions and shape	Thickness	EN 10029		EN10025-1 2004
Yield strength (transverse)	Flatness	EN 10029			
	Nominal thickness (mm)	Values Min (Mpa)			
	>	<=			
	-	16	355		
	16	40	345		
	40	63	335		
	63	80	325		
	80	100	315		
Tensile strength (transverse)	100	150	295		
	Nominal thickness (mm)	Values (MPa)			
	>	<=	min	max	
	5	100	470	630	
	100	150	450	600	
	Elongation (transverse)	Nominal thickness (mm)	Values min (%; 5.65√so)		
>		<=			
5		40	22		
40		63	22		
63		80	21		
80	150	21			
Impact strength (longitudinal)			40J at - 20°C		
Weldability CEV	Nominal thickness (mm)	Values max (%)			
	>	<=			
	-	63	0.43		
	63	100	0.45		
	100	150	0.45		
Durability	Nominal thickness (mm)	Values max (%)			
	-	150	C:0,22 Si: 0,55 Mn: 0,85 - 1,75 P: 0,035 S: 0,030 Nb: 0,060 V: 0,14 Al: 0,015 Ti: 0,060 Cr: 0,35 Ni: 0,55 Mo: 0,13 Cu: 0,60 N: 0,017		



0038

Tata Steel
Long Products Europe
PO Box 1, Brigg Road
Scunthorpe, UK

13

LPE Plate S355N

EN 10025-1 – 2004

Plate S355N / 1.0545

To be used in-welded, bolted and riveted structures

Tolerances on dimensions : Plate EN10029

Elongation :
Tensile Strength :
Yield Strength : EN10025-3
Impact Strength :
Weldability :
Durability :

Dangerous Substances : No Performance Determined